



vCamMX-2⁺

Mini-Inspection System

- Improved video and image quality
- Small profile camera heads
- Over-the-air firmware updates
- Seven-hour battery life
- Record to USB with SD card backup

The vCamMX-2⁺ Mini-camera system is versatile and compact at an affordable price. Easily inspect lines from 1-1/2 to 4" (38 to 100mm), with two interchangeable camera heads and two pushrod lengths. The vCamMX-2⁺ mini-camera features a three-frequency sonde, locatable pushrod, distance counter, internal rechargeable batteries, and a built-in voice-over microphone. The vCamMX-2⁺ produces clear, crisp videos and images using the latest HD technology.

The Type-MX reel is constructed of stainless steel with a lightweight, rugged carbon fiber pushrod drum. The dual-position reel and multiangle LCD can be used upright or horizontally. Record directly to the USB drive while creating a backup copy on the SD card or connect to the VMC app by Wi-Fi and record on the tablet or smartphone.

Internal microphone for audio commenting over recording videos

30'/10m Wi-Fi range for use with the free VMC app



8" multi angle daylight viewable display

Video out through RCA composite socket
Export distance out and video via the mini-USB port

Automatic backup of videos and pictures to SD Card

Large keypad usable while wearing gloves

Internal rechargeable battery provides seven-hours of battery life

Locatable three-frequency sonde and traceable pushrod

Available interchangeable camera heads

Field-serviceable spring assembly



D26-HD 1"/26mm self-leveling camera



D18-HD 0.70"/18mm non-leveling camera

Lightweight, durable carbon-fiber pushrod drum

- One-year warranty covers entire system
- Extended warranty is available
- Camera exchange program for out of warranty camera heads

Backed by Vivax-Metrotech's superior dealer network, customer service and service centers.

Camera Heads

	D26-HD	D18-HD
Application:	2 to 4"/50 to 101mm	1-1/2 to 3"/38 to 75mm
Dimensions:	1.02" x 1.41"/26mm x 35.9mm	0.73" x 0.71"/18.6mm x 18.1mm
Lighting:	103 Lumens	69 Lumens
Resolution:	1080p	1080p
Construction:	Stainless-steel housing with scratch-resistant Sapphire lens	
Self-leveling:	Yes	No
Environmental:	11 BAR	11 BAR
Focus point:	6"/15cm	4"/10cm
Field of view:	114°	90°

vCamMX-2+ System

Dimensions:	22.8" (L) x 15" (W) x 28" (H)/58cm x 38cm x 70cm
Weight:	100 ft. (30m): 30 lbs. (14 kg) 150 ft. (45m): 37 lbs. (17 kg)
Construction:	High impact ABS control module, stainless-steel tubular frame, with a carbon-fiber drum
Display:	8"/20cm Daylight viewable 800 x 600 TFT LCD display
Battery life:	Eight-hours with sonde off, seven-hours with sonde on
Environmental:	Water resistant to IP65 (light shower with lid closed)

Type-MX Mini-Reel

vCamMX-2+ can be purchased as a complete all-in-one unit with the control module mounted to the reel, or purchase the reel separately to use with the vCam-6 control module.



Type-MX Reel with 100ft/30m or 150ft/45m of pushrod



vCam-6 Control Module



Interconnect plugs into the vCam-6 control module



D18-HD, D26-HD camera heads

Sonde Locators



vLoc3-Cam and VM-540

Popular Accessories



D18-HD camera



Type-MX Reel Drip bag



vCam Mobile Controller App

Local Vivax-Metrotech Distributor:

Vivax-Metrotech Corporation

3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free: 1-800-446-3392

Tel: +1-408-734-3880

www.vivax-metrotech.com

Tag us on social media @vivax_metrotech



V1.0

Please visit our website for full product specifications.