



**WACKER  
NEUSON**  
*all it takes!*

## BPS1340A

5100059906

[Home](#) >> [Catalog](#) >> [Products](#) >> [Compaction](#) >> [Vibratory Plates](#) >> [Single direction Vibratory Plates](#) >> **BPS1340A**

### BPS1340A

Material number 5100059906

Single direction vibratory plate for soil and asphalt compaction.  
Honda petrol engine.



### Product details

- Excellent driving features: No matter whether used on asphalt or soil – the BPS is easy to manoeuvre and provides perfect surfaces.
- Clean finish to the kerb is easily generated due to the square side-profile of the base plate.
- The control handle addresses the steering movements clearly, yet nevertheless generates low hand-arm vibrations of less than 5 m/s<sup>2</sup>, which enable a long, comfortable working conditions.
- Easy to transport: A large lifting eye and wide, ergonomically designed carrying handles make moving and loading the machine both easy and comfortable.
- Maintenance-free: The BPS series is equipped with an extremely sturdy fan belt and has storage with lifetime lubrication. As a result, it is practically maintenance-free.
- Accessories are available separately: Wheel set and paving stone sliding mechanism round off the application areas of the APS.

### Comes with

- Vibratory plate
- Operating manual

## Technical specifications

### BPS1340A

#### MECHANICAL DETAILS

Length Drawbar in op. pos.	930 mm
Width	400 mm
Height	663 mm
Operating weight	71,0 kg
Ground clearance	663 mm

#### OPERATING FLUIDS

Tank capacity	3,60 l
---------------	--------

#### ENVIRONMENT DATA

Storage temperature range	-15 - 40 °C
Sound level LpA	95,0 dB(A)
Sound power LWA, measured	104,0 dB(A)
Sound power LWA, guaranteed	105,0 dB(A)
Operating temperature range	-15 - 45 °C
Sound power LWA (Standard)	EN 500-4
HAV summation (Standard)	EN 500-4
HAV summation (average value)	4,6 m/s <sup>2</sup>
Uncertainty in measurement HAV	0,5 m/s <sup>2</sup>

#### ELECTRICAL SYSTEM

Electrode distance	0,7 - 0,8 mm
--------------------	--------------

## ENGINE

Cooling	air cooling
Engine type	Gasoline engine
Engine operating mode	four-stroke
Cylinder capacity	163 cm <sup>3</sup>
Fuel	Gasoline
Fuel management	Carburettor
Fuel consumption	0,80 L/Std
Inclined position max.	20,0 °
Cylinder	1
Oil specification	SAE 10W-30
Oil filling max.	0,60 l
Power rating max.	3,6 kW
Standard (Effective power)	ISO 3046 IFN
Nominal Engine speed	3.600 1/min
Standard (Power max.)	SAE J1349
Operating power	2,9 kW
Engine speed (Power max.)	3.600 1/min
Effective power	2,6 kW
Oil filling min.	0,60 l
Standard (Operating power)	ISO 3046 IFN
Operating Engine speed	3.520 1/min
Exhaust-gas limit	EPA4/08
Spark plug(s)	NGK BP-6 ES
Starter battery Voltage	0 V
Starter type	Recoil starter
Oil volume incl. filter change	0,60 l
Air cleaner	dry air filter
Battery capacity (nom. value)	0 Ah

Engine Manufacturer

Honda

---

#### MECHANICAL - OUTPUT DETAILS

Centrifugal force	13,000 kN
-------------------	-----------

---

Transmission	FKR
--------------	-----

---

Vibrations	5.880 1/min
------------	-------------

---

Area capacity	624 m <sup>2</sup> /h
---------------	-----------------------

---

Forward Running	26,00 m/min
-----------------	-------------

---

Gradeability	36,4 %
--------------	--------

---

Vibrations (Hz)	98 Hz
-----------------	-------

---

#### Custom Attributes

Model serie	BPS
-------------	-----

---

#### Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2018 Wacker Neuson SE