



**WACKER
NEUSON**
all it takes!

4-stroke rammer BS60-4As, 280 mm ramming shoe

5200018232

[Home](#) >> [Catalog](#) >> [Products](#) >> [Compaction](#) >> [Vibratory Rammers](#) >> [4 Stroke Rammer](#) >> [4-stroke rammer BS60-4As, 280 mm ramming shoe](#)

4-stroke rammer BS60-4As, 280 mm ramming shoe

Material number 5200018232

Four-stroke vibratory rammer with 280 mm ramming shoe for soil compaction, Honda GX engine



Product details

- Long shoe stroke, high percussion rate and high impact energy with fast advance travel achieve high performance results
- Low oil protection: Unit will not start if sensor detects no oil or low oil, protecting the engine
- Simple operation with only one lever for acceleration and shutoff
- Powered by Honda GX 100 engine and designed for the compaction of cohesive, mixed and granular soils in confined areas
- Unique four-stage air filtration system provides longer life and improved durability

Comes with

- Vibratory rammer
- Operator's Manual

Errors and omissions are reserved. The information in this data sheet is based on present knowledge. However, this neither guarantees specific product features nor establishes a legally valid contractual relationship.

Technical specifications

4-stroke rammer BS60-4As, 280 mm ramming shoe

SHIPPING AND STORAGE

Shipping weight	80,00 kg
-----------------	----------

MECHANICAL - OUTPUT DETAILS

Number of blows	690 1/min
-----------------	-----------

MECHANICAL DETAILS

Length	673 mm
--------	--------

Length Ramming Shoe	336 mm
---------------------	--------

Width	343 mm
-------	--------

Width Ramming Shoe	280 mm
--------------------	--------

Height	965 mm
--------	--------

Weight	72,00 kg
--------	----------

stroke at tamper	78 mm
------------------	-------

OPERATING FLUIDS

Tank capacity	3,00 l
---------------	--------

ENVIRONMENT DATA

Sound level LpA	91,0 dB(A)
-----------------	------------

Sound power LWA, measured	104,0 dB(A)
Sound level LpA (Standard)	EN 500-4
Sound power LWA, guaranteed	108,0 dB(A)
Sound power LWA (Standard)	2000/14/EG
HAV summation (Standard)	EN ISO 5349-1
HAV summation (average value)	6,5 m/s ²

ENGINE

Cooling	air cooling
Engine type	Gasoline engine
Engine operating mode	four-stroke
Cylinder capacity	98 cm ³
Fuel	Gasoline
Fuel management	Carburettor
Fuel consumption	0,90 L/Std
Cylinder	1
Oil specification	SAE 10W-30
Oil filling max.	0,40 l
Operating power	2,4 kW
Effective power	2,4 kW
Oil filling min.	0,40 l
Operating Engine speed	4.200 1/min
Exhaust-gas limit	EPA Phase2 & EU2002/88/EC
Starter type	Recoil starter
Air cleaner	dry air filter
Engine Manufacturer	Honda
Electrode distance	0,6 - 0,7 mm

Custom Attributes

Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2018 Wacker Neuson SE