



**WACKER
NEUSON**
all it takes!

Wet screed P35A

5000620957

[Home](#) >> [Catalog](#) >> [Products](#) >> [Concrete Technology](#) >> [Vibratory Screeds](#) >> [Wet Screeds](#) >> **Wet screed P35A**

Wet screed P35A

Material number 5000620957

Gasoline power unit wet screed used to fit with a variety of blades for finishing concrete slabs, Honda engine



Product details

- Twin handle system is fully height and angle adjustable to for operator comfort
- Shock mounted to reduce vibration to the operator
- Lightweight, squeeze grip handle is also foldable for easy storate and transport
- Seven position adjustabl eccetric weights allows operator match the unit's force with the application
- Fully enclosed exciter for low maintenance

Comes with

- P35 Power Unit
- Mounting Hardware for Blade
- Operator's Manual

Technical specifications

Wet screed P35A

ENGINE

Cooling	air cooling
Engine type	Gasoline engine
Engine operating mode	four-stroke
Cylinder capacity	36 cm ³
Fuel	Gasoline
Fuel consumption	0,60 L/Std
Cylinder	1
Tank capacity	0,60 l
Oil specification	SAE 10W-30 API SJ
Power rating max.	1,0 kW
Engine speed (Power max.)	7.000 1/min
Standard (Operating power)	SAE J1349
Starter type	Recoil starter
Engine Manufacturer	Honda
Running time at 100%	1,1 std

SHIPPING AND STORAGE

Height for shipping	622 mm
Width for shipping	483 mm
Length for shipping	668 mm
Shipping weight	18,60 kg

MECHANICAL DETAILS

Length	94 mm
Width	94 mm
Height	90 mm
Operating weight	14,1 kg

Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2018 Wacker Neuson SE